

TILTING TABLE. ELECTRICAL SYSTEM WITH SEPARATE 24V CIRCUIT FOR ON-BOARD MACHINE CONTROLS.



<b>Max drilling capacity on cast iron with pre-drilling hole</b>	Ø 32 mm
<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	Ø 28 mm
<b>Continuous drilling capacity</b>	Ø 20 mm
<b>Spindle taper</b>	CM 4
<b>Chuck sizes</b>	5 - 20 mm B22
<b>Spindle speed</b>	(12) 150 - 2450 rpm
<b>Spindle travel</b>	120 mm
<b>Quill</b>	Ø 62 mm
<b>Column</b>	Ø 92 mm
<b>Height</b>	1710 mm
<b>Distance column-chuck</b>	260 mm
<b>Table dimensions</b>	460 x 425 mm
<b>Slot</b>	14 mm
<b>Tilting table</b>	± 45°
<b>Motor</b>	400 V 50 Hz 1,5 kW
<b>Net weight</b>	126 kg
<b>Packaging dimensions</b>	1430x660x350 h mm
<b>Gross weight</b>	122,50 kg
<b>EAN Code</b>	8012667213558

**Included**

Keyless chuck 5 - 20 mm B22  
Drill chuck shank MT 4